

Product Description

CGPC PVC H-58 is a Polyvinyl Chloride material. It is available in Asia Pacific or North America for blow molding or injection molding.

Typical applications include:

- Bottles
- Engineering/Industrial Parts

General

Material Status	• Commercial: Active		
Availability	• Asia Pacific	• North America	
Uses	• Blow Molding Applications	• Bottles	• Fittings
Processing Method	• Blow Molding	• Injection Molding	

Physical

	Nominal Value	Unit	Test Method
Apparent (Bulk) Density		g/cm ³	ISO 60
K-Value			ISO 1628-2
Particle Size - 45 Mesh Pass ²		%	
Volatiles		%	ISO 1269

Additional Information

	Nominal Value	Unit	Test Method
Degree of Polymerization			
Residual Vinyl Chloride Monomer		ppm	ISO 6401

Available Documents

Technical Datasheet (English)

Notes

¹ Typical properties: these are not to be construed as specifications.

² Honeywell SRA-150

UL and the UL logo are trademarks of UL LLC © 2020. All Rights Reserved.

The information presented here was acquired by UL from the producer of the product or material or original information provider. However, UL assumes no responsibility or liability for the accuracy of the information contained on this website and strongly encourages that upon final product or material selection information is validated with the manufacturer. This website provides links to other websites owned by third parties. The content of such third party sites is not within our control, and we cannot and will not take responsibility for the information or content.